



# Safelift 360° 'Award winning' HAND CHAIN HOISTS

## Revolutionary hand chain hoist design!

With our innovative new design the Safelift 360 opens up a new world of safety for the operator. The range of applications as well as the operating conditions have been changed by a revolutionary hand chain guide system.

The key to this innovation is our revolutionary 360° rotating hand chain guide which allows operation of the hand chain from virtually any position, even in extremely confined areas. The Safelift 360 can be operated at the side of the load or from any other position including horizontal pulling. **The plane between top and bottom hook must always be in a straight line.**



**More flexibility gives greater safety - operators can now work outside of the immediate danger zone reducing the risk of operator injury.**



Product code	Capacity (SWL) kgs	Falls of load chain	Load chain mm	Closed height mm	Weight @ 3 mtr HOL kgs
004700001	500	1	5 x 15	300	9
004700003	1000	1	6 x 18	335	13
004700005	2000	1	8 x 24	395	20
004700007	3000	1	10 x 30	520	29
004700008	5000	2	10 x 30	640	38
004700010	10000	3	10 x 30	825	71
004700049	20000	6	10 x 30	980	196

- All Safelift hoists are chained to suit your specific requirements. The standard length is 3 mts but you can specify any height of lift. Please call our sales team with your requirements.
- Chain containers are NOT supplied as standard but are available on request.



## YLITP INTEGRAL PUSH TROLLEY HOISTS

Product code		Capacity (SWL) kgs	Falls of load chain	Beam width		Closed height mm	Weight	
Type A	Type B			Type A mm	Type B mm		(A) mm	(B) mm
YLITPA500	YLITPB500	500	1	50-180	180-300	245	20	21
YLITPA1000	YLITPB1000	1000	1	58-180	180-300	272	27	29
YLITPA2000	YLITPB2000	2000	1	58-180	180-300	323	44	46
YLITPA3000	YLITPB3000	3000	1	74-180	180-300	382	77	79
YLITPA5000	YLITPB5000	5000	2	98-180	180-300	550	125	129



## YLITG INTEGRAL PUSH TROLLEY HOISTS

Product code		Capacity (SWL) kgs	Falls of load chain	Beam width		Closed height mm	Weight	
Type A	Type B			Type A mm	Type B mm		(A) mm	(B) mm
YLITGA500	YLITGB500	500	1	50-180	180-300	245	24	25
YLITGA1000	YLITGB1000	1000	1	58-180	180-300	272	32	33
YLITGA2000	YLITGB2000	2000	1	58-180	180-300	323	49	50
YLITGA3000	YLITGB3000	3000	1	74-180	180-300	382	82	84
YLITGA5000	YLITGB5000	5000	2	98-180	180-300	550	130	134
-	YLITGB10000	10000	3	-	125-300	776	-	175

\* Available in Push or Geared travel and as Standard finish or Corrosion Resistant.

The combination of the Safelift 360 with a low headroom manual trolley provides even more flexibility in the application of this revolutionary hoist. All units up to 3000kgs are provided with a single fall of load chain and the headroom has further been reduced. Ideal for applications with low ceilings and limited headroom. The manual trolleys are adjustable to fit a wide range of beam profiles (e.g. INP, IPE, IPB). Depending on the beam flange width an adjustment up to 300mm can be easily made. Anti-tilt and anti-drop devices are fitted as standard.