



HTP ^{'Standard'} PUSH TRAVEL TROLLEYS



Product code	Capacity (SWL) kgs	Beam width mm	Weight kgs	Product code	Capacity (SWL) kgs	Beam width mm	Weight kgs
Type 'A'				Type 'B'			
05141273	500	50 - 220	8	05148305	500	160-300	10.6
05141274	1000	58 - 220	9	05148306	1000	160-300	12
05141275	2000	66 - 220	16	05148307	2000	160-300	19.3
05141276	3000	74 - 220	32	05148308	3000	180-300	35.8
05141277	5000	90 - 220	48	05148309	5000	180-300	52.2



HTG ^{'Standard'} GEARED TRAVEL TROLLEYS



Product code	Capacity (SWL) kgs	Beam width mm	Weight kgs	Product code	Capacity (SWL) kgs	Beam width mm	Weight kgs
Type 'A'				Type 'B'			
05300006	500	50 - 220	9.7	05300011	500	160-300	12.6
05300007	1000	58 - 220	11.2	05300012	1000	160-300	14.1
05300008	2000	66 - 220	18	05300013	2000	160-300	21.3
05300009	3000	74 - 220	35.	05300014	3000	180-300	39.2
05300010	5000	90 - 220	51.8	05300015	5000	180-300	56
-	-	-	-	-	10000	125-310	104
-	-	-	-	-	20000	125-310	230

- 2.5 metre hand chain drop as std. to suit 3 metre HOL.
- Additional metre HOL of HTG hand chain is available. Call Rossendale sales team for details.
- Optional track clamp for HTP/HTG trolleys 500 - 5000kgs is also available on request.
- Optional lock nuts for HTP/HTG trolleys 500 - 2000kgs are also available on request.



YC ^{'Standard'} BEAM CLAMPS



Product code	Capacity (SWL) kgs	Beam width mm	Weight kgs
05406181	1000	75 - 230	3.8
05406182	2000	75 - 230	4.6
05407417	3000	80 - 320	9.2
05407418	5000	90 - 320	11.0
05407419	10000	90 - 320	17.2

The YC beam clamp provides a quick and versatile rigging point for hoisting equipment, pulley blocks or loads and comes complete with a locking device. Flexible application due to the wide adjustment range. Central threaded spindle allows easy attachment and a safe and secure grip.



CTP ^{'Integral'} PUSH TROLLEY BEAM CLAMPS



The easy installation to any beam makes the CTP suitable for fixing to any hoists, pulleys and loads you wish to move. It can be adjusted quickly to the beam width by turning the main spindle. Safety is ensured by the special locking lever. The spindle and snap-pin stops are galvanised to protect against corrosion. The **CTP-2A** trolley clamp has undergone rigorous testing at the national engineering laboratory and complies with EN 795 Class B and BS EN 3795 and is therefore suitable for man riding applications.

* The CTP-2M is now certified for man riding.

Product code	Model	Capacity (SWL) kgs	Beam width mm	Min. curve radius mm
005500024	CTP - 1A	1000	60 - 150	0.9
005500025	CTP - 2A	2000	75 - 200	1.15
005500025M	CTP - 2M	2000	75 - 200	1.15
005500026	CTP - 2B	2000	200 - 300	1.15
005500027	CTP - 3A	3000	75 - 200	1.4
005500028	CTP - 3B	3000	200 - 320	1.4