



safe lift **D85** 'The Original' **PUL-LIFTS**

Product code	Capacity (SWL) kgs	Falls of load chain	Load chain mm	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs
01541291	750	1	6 x 18.5	1.5	322	11
01541292	1500	1	9 x 27	1.5	389	16
01541293	3000	1	11 x 31	1.5	403	23
01541294	6000	2	11 x 31	1.5	532	46
01451511	10000	3	11 x 31	1.5	805	69

The D85 Pul-Lift is the original ratchet lever hoist. The enclosed housing cover, handlelever and lower block are made from high ensile white malleable cast iron providing overall rugged construction. The graphite cast iron load sheave for the link chain has precision machined chain pockets for accurate fit and durability of load chain. The D85 is designed for heavy duty work and is suitable for almost any application in maintenance, mining, construction, steel fabrication, shipbuilding, utility work and especially in the railway industry.



*
Low effort
required on
handlelever

safe lift **AL** 'Aluminium' **RATCHET LEVER HOISTS**

Product code	Capacity (SWL) kgs	Falls of load chain	Load chain mm	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs
002041258	750	1	6.3 x 19.1	1.5	315	6.4
002041259	1000	1	6.3 x 19.1	1.5	325	6.6
002041260	1500	1	7.1 x 21.2	1.5	380	10
002041261	3000	1	10 x 30.2	1.5	455	18

Enclosed housing, handlelever and handwheel are made from high quality aluminium. Due to precise needle bearings the hoist can be operated with little effort. Its low tare weight is an advantage when the hoist has to be carried over longer distances on different assignments. Chain guide is cast into the body to ensure faultless chain movement. The free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions.



safe lift **PT** 'Pressed steel' **RATCHET LEVER HOISTS**

Product code	Capacity (SWL) kgs	Falls of load chain	Load chain mm	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs
002200001	800	1	5.6 x 17.1	1.5	290	5.5
002200002	1600	1	7.1 x 21.2	1.5	330	9.6
002200003	3200	1	9 x 27.2	1.5	430	16
002200004	6300	2	9 x 27.2	1.5	580	31

The PT is probably the most universal ratchet lever hoist in the Safelift range. The pressed steel housing provides an extremely low weight. The standard free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions. Low operating effort and low overall height are further outstanding features. The PT really is a good, versatile, all round ratchet lever hoist suitable for almost all standard applications.



safe lift **UNO** 'Budget' **RATCHET LEVER HOISTS**

Product code	Capacity (SWL) kgs	Falls of load chain	Load chain mm	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs
002300001	750	1	6 x 18	1.5	350	7
002300002	1500	1	8 x 24	1.5	420	11
002300003	3000	1	10 x 30	1.5	520	21
002300004	6000	2	10 x 30	1.5	700	28

The UNO is a versatile ratchet lever hoist designed for pulling, lifting and lashing of loads. Its features include a compact design, robust stamped steel construction and a favourable price/efficiency ratio. The unit is also very lightweight and comes complete with a free chaining device as standard that serves to quickly attach the load or to pull the chain through the hoist in both directions.