



Concrete pipe lifting clamps

Working load limit (WLL) 1500 - 3000kgs*

The BTG concrete pipe lifting clamps are sold in sets of three and they come complete with chain slings (the working load limits shown are based on a set of three clamps).

They are designed for the vertical transportation of concrete pipe sections with a diameter of upto 3000mm.

The jaw capacity is designed for pipe thickness of 40 - 200 mm.

Attachment and removal of the clamps from the pipes is extremely easy due to the simple and straightforward design.

Features include:

- ✓ Solid construction.
- ✓ Type-tested 4 to 1 against breakage.
- ✓ Simple and safe handling.
- ✓ Large jaw capacity.
- ✓ For heavy duty use.
- ✓ Lightweight design.
- ✓ Service friendly.
- ✓ For concrete according to DIN4034

* Lifting clamps for concrete pipe up to a diameter of 3000mm are available upon request.

Workmanship and parts

These pipe lifting clamps are service-friendly, making them easy to exchange parts, which are readily available. Clamp repairs are available through Rossendale Group repair and test facilities.

Model	Product code	WLL capacity kgs*	Jaw (Z) mm	Mouth depth (E) mm	Pressure line (F) mm	A mm	B mm	C mm	D mm	Weight kgs**
BTG1500/3	54609200	1500	40 - 120	165	100	135	75	18	180	34
BTG3000/3	54609204	3000	50 - 180	245	175	180	100	26	310	60
BTG3000L/3	54609206	3000	90 - 220	245	175	180	100	26	310	78

*Per set of three

**Weight per set of three c/w chains

